



TITAN[®]
ADVANCED STRIPING EQUIPMENT

THERMOMARK **HD1500**



THERMOPLASTIC RIDE-ON LINE APPLICATOR WITH A 1,500 LB. RESERVOIR

The ThermoMark HD1500 is a mid-sized ride-on applicator with a large melting capacity providing 1,500 lbs. of hot thermoplastic for long line production.

Exclusive Features

- 1,500 lbs. of material at $\pm 400^{\circ}$
- Hydrostatic drive provides smooth operation at any speed
- Uses one fuel (diesel) for the engine drive and melting systems
- Oil jacketed from the kettle to the die (kettle, supply lines and dies)
- Two rear independent drive motors handle heavy loads with ease
- Standard with a programmable electronic skip timer
- Versatile two-sided seating
- Pressurized bead dispenser (200 lb. capacity)
- Applies single or double lines
- Choose from ribbon extrude, screed extrude or profile extrude dies



Specifications

Weight	6,600 lbs.
Dimensions	146"L x 89-94"W x 78"H
Construction	Steel
Engine	Kubota diesel 46 HP
Transmission	2 speed hydrostatic
Material Capacity	1,500 lbs. / 100 gal.
Fuel Tank	30 gal.
Air Compressor	28 CFM
Heating System	Diesel
Glass Bead System	200 lbs. pressurized
Steering	Dual left and right



Additional Features

- ▶ 1,500 lbs. of material at $\pm 400^{\circ}$
- ▶ Fortified midsize chassis design
- ▶ Rugged, dependable and precise
- ▶ Kubota turbo diesel engine
- ▶ Heavy duty front axles
- ▶ 13" tires and rims
- ▶ Onboard melting capability
- ▶ 30 gallon diesel tank
- ▶ Large kettle size (1,500 lbs. / 100 gal.)
- ▶ Rear hydrostatic drive motors
- ▶ Rubber mounted engine frame
- ▶ Large capacity radiator with hydraulic cooler
- ▶ Electronic skip timer
- ▶ 1" king pins
- ▶ Electric toggle switch controls
- ▶ Speed control
- ▶ Fluid drive pedals
- ▶ No loose linkage

SL40523 JB70971B