VOL. 125

FULL LINE CATALOG



SCAN FOR DIGITAL COPY





THE BEST AND LONGEST WARRANTY IN THE INDUSTRY

Four-Year Manufacturer's Defect

We pledge that our sprayers are free from defects in materials and workmanship. This excludes normal wear items and consumables such as filters, piston, packings, spray tips, spray guns, hoses, etc.

Lifetime DuraLife HE and PMDC Motor Warranty

If the motor fails for any reason (including wear) for as long as you own the sprayer, we will replace the motor at no cost to you.

Limited Lifetime DCX Motor Warranty

If the motor fails from normal usage for as long as you own the sprayer, we will replace the motor at no cost to you.

Lifetime Drive Train Warranty

If the drive train fails from normal usage for as long as you own the sprayer, we will replace the drive train at no cost to you.

Lifetime Warranty on PermaStroke Technology[™] Fluid Pump

Get a lifetime warranty on the PermaStroke Technology fluid pump. If the fluid pump fails for any reason (including wear) for as long as you own the sprayer, we will replace the fluid pump at no cost.

Two-Year Turbine Warranty

Gas Engine Warranty

Three-year Honda[®] and two-years all others.

AMPShare by Bosch[®] Warranty

Three-year limited warranty on batteries and fiveyear limited warranty on battery chargers.

Honda eGX System Warranty

Honda provides a 3 year warranty on their eGX motors, and a 2 year warranty on eGX batteries and eGX chargers.

35-Day Satisfaction Guarantee

If for any reason the sprayer does not perform up to your expectations within 35 days, the sprayer can be exchanged for the identical model or full credit toward the purchase of a Titan sprayer of larger size and value.

Express Parts Program

- More than 550 Authorized Service Centers nationwide
- The most common repair parts are guaranteed to be in stock 100% of the time
- If for any reason your preferred Authorized Service Center is out of stock, free 2nd day air is available when ordered by 3:00 pm (EST)

GO TO TITANWEARGUARD.COM FOR MORE INFORMATION



04 IMP

IMPACT X[™]

Taking jobsite performance to the next level with features that enhance performance X-ponentially.

05 IMPACT INTELLISYNC®

These fully featured sprayers offer the ultimate in functionality and convenience.

06 IMPACT[®]

Durable electric airless sprayers built with smart features that make an Impact.

POWRTWIN[™] For large-scale residential, commercial and industrial applications.

08

በ7

POWRTWIN DI The most powerful portable sprayers on the market today.

08 POWRBEAST°

Heavy-duty direct immersion sprayers capable of spraying light- to heavy-bodied coatings.

09 ELITE[®] Perfect fo

Perfect for the pro that never wants to replace the sprayer's piston, packings, cylinder, or clutch.

10 HYDRA X[™] The ultimate sprayers for any job where maximum power is required.

1 BATTERY-POWERED

Portable sprayers outfitted with Powerful AMPShare[™] by Bosch[®] 18V batteries.

12 CAPSPRAY[™] Maximize productivity and profit with these lightweight, portable sprayers.

13 FINE FINISHING Delivers beautiful finishes quickly and easily.

POWRCOAT[™] Pneumatic sprayers for virtually any heavy-duty application.

15 POWRLINER[™] A broad line of pavementand turf-marking equipment for all size projects.

16 AIRLESS GUNS Guns that deliver a perfect finish the first time–every time.

18

AIRLESS TIPS Renowned in the industry for their fan pattern consistency and long life.

OUR MISSION

When your business depends on the tools you use, you need to be able to count on the people who make them.

Our relentless commitment to helping every professional painter be their best leads to better work, improved ROI and growing business.

All information contained in this brochure is based on the latest information available at the time of printing. Titan reserves the right to make changes at any time, without notice. Due to continuous innovation, specifications may progressively change. Contact one of our dependable sales reps or call our dedicated customer service team for more information.

IMPACT X[™] SERIES

Features:

MaxFX[™] Fluid Section

Quick-change fluid section that is replaceable in minutes on the jobsite



DuraLife™ HE Brushless Motor

Optimized for every tip size and every painter's technique



Logix™ Adaptive Pressure Control System

Enhances performance through innovative tip-sensing technology

Vertical Filter Housing

Completely drains coatings and maximizes filtering area ensuring full filtration of material

Connects sprayer to the MyTitan mobile app (Available on 540) only)





	Impact X 410	Impact X 440	lmpact X 540I
SPECIFICATIONS			
Max. Delivery	0.47 gpm	0.54 gpm	0.54 gpm
Max. Tip Size (1-Gun)	0.021"	0.023"	0.023"
Max. Operating Pressure	3300 psi	3300 psi	3300 psi
Gun Included	RX-80	RX-80	RX-Pro
Motor (120V)	7/8 hp DuraLife HE Brushless	1.20 hp DuraLife HE Brushless	1.20 hp DuraLife HE Brushless
CONFIGURATIONS		PART NO.	
Skid	2430897	2429069	2431656
High Rider	2430869	2430510	2431657
Low Rider			2431658

All configurations come with a 517 HEA Tip and 1/4" x 50' airless hose.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Titan is under license. Other trademarks and trade names are those of their respective owners.

THE NEXT GENERATION

Multiply your productivity Xponentially with the Xtended line of Impact sprayers, now with more variety and more options. They're the Impact sprayers you know and love re-engineered and reimagined for the future. Spray faster, smarter, and better every time.





IMPACT INTELLISYNC® SERIES

Features:

Field Serviceable Fluid Section

 $\mathsf{EasyOut}^{\scriptscriptstyle \mathsf{M}}$ Fluid section is easy to replace on the jobsite, no tools required

DuraLife[™] HE Brushless Motor

Optimized for every tip size and every painter's technique

Logix[™] Adaptive Pressure Control System

Enhances performance through all-new tip-sensing technology

Digi-Trac[™] Digital Display Available on I models only No pressure fluctuation, X-Lock anti-theft and resettable gallon counter and hour meter



Auto0iler[™]

Deliver oil to the packings with the push of a button.

INTELLISYNC Bluetooth

Connects sprayer to the MyTitan mobile app

😡 ACTIVGUARD

Integrated GPS system gives your real-time location of sprayer (Available on Impact IA models only)

CONNECTED APP-DRIVEN SPRAYERS

These fully featured sprayers offer the ultimate in functionality and convenience for the longest days and biggest projects. Capable of supporting large tip sizes and multiple guns, you can rely on the power and performance of the Impact Intellisync sprayers.



	Impact 6401 & IA	Impact 8401 & IA	Impact 1140ı & IA
SPECIFICATIONS			
Max. Delivery	0.70 gpm	1.00 gpm	1.20 gpm
Max. Operating Pressure	3300 psi	3300 psi	3300 psi
Max. Tip Size (1-Gun)	0.027"	0.032"	0.034"
Max. Tip Size (2-Guns)		0.021"	0.023"
Gun Included	RX-Pro	RX-Pro	RX-Pro
Motor (120V)	1.55 hp DuraLife HE Brushless	2.3 hp DuraLife HE Brushless	2.6 hp DuraLife HE Brushless
CONFIGURATIONS	PART NO.	PART NO.	PART NO.
Skid I	2419187		
Skid IA	2418753		
High Rider I	2419194	2419303	2419294
High Rider IA	2419011	2419222	2419291
Low Rider I	2419039	2419300	2454245
Low Rider IA	2419038	2419297	2454244



All configurations come with a 517 HEA Tip and 1/4" x 50' airless hose.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Titan is under license. Other trademarks and trade names are those of their respective owners.

IMPACT[®] SERIES

Features:

Field Serviceable Fluid Section

One-piece polyethylene packings and no cylinder to wear out

DuraLife[™] HE Brushless Motor

Optimized for every tip size and every painter's technique

Auto0iler[™]

Deliver oil to the packings with the push of a button





	Impact 740		lmpact 1040T	
SPECIFICATIONS				
Max. Delivery	0.80 gpm	1.15 gpm	1.15 gpm	
Max. Tip Size (1-Gun)	0.029"	0.033"	0.033"	
Max. Tip Size (2-Guns)	0.019"	0.022"	0.022"	
Max. Operating Pressure	3300 psi	3300 psi	3300 psi	
Gun Included	RX-Pro	RX-Pro	RX-Apex [™] Non-Filter	
Motor (120V)	2.00 hp DuraLife HE Brushless	2.50 hp DuraLife HE Brushless	2.50 hp DuraLife HE Brushless	
CONFIGURATIONS	PART NO.	PART NO.	PART NO.	
High Rider	805-007	552600	2405360	
Low Rider		2453769		

Impact 740 and 1040 come with 517 HEA and 1/4" x 50' hose.

Impact 1040T comes with RX-Apex, SC-6+ 427 & 531, splatter nozzle, 1/4" x 6' whip hose and 3/8" x 50' airless hose

Business is demanding and you need the kind of performance you expect from Titan sprayers. It's time to invest in the expanded features and performance that will make a major IMPACT on your profit margin.





POWRTWIN[™] SERIES

Features:

Severe Service[™] 900 Pump

Cylinder and piston rod are tempered with a proprietary heat-treating process that increases pump life 150% over competitive pumps

1

Self-adjusting packings prevent over-tightening and help prevent wear

Speeflo[®] HydraDrive[™]

Smooth, slow-stroking hydraulic drive provides extreme power and reliability

Accurate Pressure Control

- Adjust operating pressure from 400 to 3300 psi and spray low viscosity primers to heavybodied finish paints
- For even more power, the PowrTwin 12000 Plus provides an operating pressure up to 3600 psi

Long Life & Durable

Longest stroking portable sprayer in the market

Convertible

Easy, tool-free convertibility for projects where gas engines are not permitted Optional convertor kits sold separately



Pivotable housing provides easy access for belt replacement and power source conversion



Heavy-Duty Frame

Durable cart with telescoping handle and convenient lift handles

HYDRAULIC PISTON SPRAYERS

Since their introduction almost half a century ago, PowrTwin hydraulic piston sprayers have a well-earned reputation for durability and dependability among serious contractors for largescale residential, commercial and industrial applications. Each sprayer supports multi-gun usage and quickly converts between electric and gas power.





	ELECTRIC	ELECTRIC POWERED		GAS POWERED			
	PowrTwin 6900 Plus	PowrTwin 8900 Plus	PowrTwin 4900 Plus	PowrTwin 6900 Plus	PowrTwin 8900 Plus	PowrTwin 12000 Plus	
SPECIFICATIONS							
Max Delivery	1.25 gpm	1.25 gpm	1.50 gpm	2.25 gpm	2.50 gpm	3.15 gpm	
Max Operating Pressure	3300 psi	3600 psi					
Max Tip Size (1-Gun)	0.033"	0.034"	0.044"	0.050"	0.054"	0.058"	
Max Tip Size (2-Guns)	0.023"	0.024"	0.031"	0.035"	0.038"	0.040"	
Max Tip Size (3-Guns)	0.019"	0.020"	0.025"	0.029"	0.032"	0.034"	
Max Tip Size (4-Guns)				0.025"	0.028"	0.030"	
Power Source	2 hp, TEFC DC motor	2 hp, TEFC DC motor	Honda GX160	Honda GX160	Honda GX200	Honda GX270	
Gun Included	RX-Pro	RX-Pro	RX-Pro	RX-Pro	RX-Pro	RX-Apex, non-filtered	
Part Number	290028	290027	290012	290013	290018	290016	

All configurations come with a 517 HEA Tip and 1/4" x 50' airless hose.



POWRTWIN DI SERIES

With multi-gun support and an efficient direct immersion siphon system capable of spraying very heavy coatings like drywall compound and elastomerics, these are the most powerful portable sprayers on the market today.



12000 Plus DI

POWERED by HONDA

Features:

Direct Immersion

Submersed foot valve siphons heavy viscosity coatings

Multiple Spray Guns

With an industry-leading 3.15 gpm, the 12000 Plus DI supports up to 6 spray guns

Easy to Convert

Tool-free ability to quickly swap between a gas engine and an electric motor

Note: Optional ConvertoKits sold separately.

Belt Guard

Pivotable housing provides easy access for belt replacement and power source conversion



EZ Swing Frame

Minimizes spillage during paint changes and facilitates convenient transportation

	ELECTRIC POWERED	GAS POWERED		
	PowrTwin 6900 Plus Dl	PowrTwin 6900 Plus Dl	PowrTwin 12000 Plus Dl	
SPECIFICATIONS				
Max Delivery	1.25 gpm	2.25 gpm	3.15 gpm	
Max Operating Pressure	3300 psi	3300 psi	3600 psi	
Max Tip Size (1-Gun)	0.033"	0.050"	0.058"	
Max Tip Size (2-Guns)	0.023"	0.035"	0.040"	
Max Tip Size (3-Guns)	0.019"	0.029"	0.034"	
Max Tip Size (4-Guns)		0.025"	0.030"	
Power Source	2 hp, TEFC DC motor	Honda GX160	Honda GX270	
Gun Included	RX-Apex, non-filtered	RX-Apex, non-filtered	RX-Apex, non-filtered	
Part Number	290029	290021	290023	

All configurations come with a 517 Tip and 3/8" x 50' airless hose

POWRBEAST[®] SERIES

These heavy-duty, direct immersion hydraulic piston sprayers are the preferred choice for serious contractors, who need more power and durability for large-scale jobs.



PowrBeast 💼

9700

HONDA



HydraStroke[®] Technology

- Unmatched durability and performance powered by electronically-controlled hydraulics
- Unlike clutch units that small tips can damage, PowrBeast has the versatility to spray heavy and light-bodied coatings easily
- Hydraulic motor is optimized with one moving part, reducing heat and extending life

Severe Service[™] Fluid Section

- Slow-stroking piston maximizes power and durability
- Proven Titan self-adjusting packing technology extends time between repacks
- ▶ Field serviceable with easy to remove/replace fluid section

Intelligent Design

- Extremely efficient cooling system
- Large 12" pneumatic tires increase portability and make traveling over rough surfaces easier
- Simplified pump assembly for easier service

	PowrBeast 9700
SPECIFICATIONS	
Max. Delivery	3.00 gpm
Max. Operating Pressure	3300 psi
Max. Tip Size (1-Gun)	0.055"
Max. Tip Size (2-Guns)	0.039"
Max. Tip Size (3-Guns)	0.031"
Max. Tip Size (4-Guns)	0.027"
Max. Tip Size (5-Guns)	0.023"
Power Source	Honda GX270
Gun Included	RX-Pro
Part Number	537007

All configurations come with a 517 Tip and 1/4" x 50' airless hose.

ELITE[®] SERIES

ELITE 2000

The most recent offering in Titan's Elite Series of sprayers features the Elite technology that contractors have trusted for years in a new compact design perfect for Residential, Light Commercial, and Fine Finish application.



ELITE 3000

Perfect for everyday use on residential, property maintenance and small commercial applications applying most architectural coatings such as interior and exterior latex, stains, lacquers, sealers, enamels and primers with ease.





ELITE 3500 POWERED by HONDA

The perfect sprayer for the contractor who is looking for a lightweight, gas-powered sprayer for small to medium-sized jobs.



Features:

PermaStroke Technology™

- No piston or packings, cylinder or clutch to wear or burn out
- Delivers top performance at pressures from 300 to 3300 psi and when using small or large tip sizes
- Eliminates deadband delivering a consistent fan pattern optimizing finish quality

Field Serviceable

Cartridge-style inlet and outlet valves can be changed in less than 5 minutes

FlatLine Pulsation Dampener[™] (Available on Elite 3500)

- Eliminates all pressure fluctuations in the system
- Provides smooth operation and a consistent finish

Sureflo[™] Pusher Valve

Makes system priming easy

Mechanical Pressure Control

Simple, durable and reliable with no electronics

	Elite 2000	Elite 3000	Elite 3500
SPECIFICATIONS			
Max Delivery	0.47 gpm	0.60 gpm	0.75 gpm
Max Tip Size	0.021"	0.025"	0.027"
Max Operating Pressure	3000 psi	3300 psi	3300 psi
Power Source	1.0 hp DCX	1.2 hp DCX	Honda [®] GX120
Gun Included	RX-80	RX-Pro	RX-Pro
CONFIGURATIONS	PART NO.	PART NO.	PART NO.
Skid	2437317		
High Rider		2402333	0537012A
Low Rider			0537013A

Each Elite model comes with a 517 HEA Tip and 1/4" x 50' airless hose.

HYDRA X[™] SERIES

DIRECT IMMERSION HYDRAULIC SPRAYERS

The Hydra X Series from Titan maximizes your efficiency on the jobsite with a Direct Immersion System, which means no transfer pumps, flexible siphon tubes, or air compressors are needed. It features limit-sensing hydraulics for better control, interchangeable fluid sections, and the AutoLift[™] system that raises and lowers the fluid section with the push of a button. When the job calls for the toughest coatings, the Hydra X delivers more.

Features:

HydraStroke[®] Technology

- Unmatched durability and performance powered by electronically controlled hydraulics
- Unlike clutch units that small tips can damage, the Hydra X has the versatility to spray heavy and light bodied coatings with ease
- Hydraulic motor is optimized with one moving part, reducing heat and extending life

Severe Service[™] Fluid Section

- 5" long slow piston stroke maximizes power and efficiency to extend the pump life
- Uses a tri-chrome process to create the industry's most durable fluid section with packings designed specifically for aggressive coatings
- Proven Titan self-adjusting packing technology with over 45 years in the field extends time between repacks
- New, patent pending, quick removal fluid section allows one person to service on the jobsite with ease

Smart Design

- One sprayer with modular fluid sections allowing for two different performance levels out of one sprayer
- Large 12" pneumatic tires make it easy to move around jobsite



AutoLift[™] System

- Effortless changeover for 55 gallon drums or 5 gallon pails
- Raise and lower the fluid section & hydraulic motor pump with the touch of a button

Extremely Efficient Cooling System

- Two cooling fans maximize air flow over hydraulic system
- Large 6 gallon hydraulic fluid reservoir



Hydra X 4540

High-production unit for all architectural coatings, dry wall mud, epoxies, mastics and elastomeric roof coatings

💼 Hydra X 7230

Use if you're primarily spraying: acrylic elastomeric roof coatings, asphalt emulsion, zinc coatings, or commercial architectural coatings

Hydra X 7230

Powerful high pressure sprayer for hard to atomize materials like silicone and epoxies

Use if you're primarily spraying: silicone, epoxy, or elastomeric

	Hydra X 4540	Hydra X 7230
SPECIFICATIONS		
Max. Delivery	4.0 gpm (15.1 lpm)	3.0 gpm (11.4 lpm)
Max Tip Size (1-Gun)	0.067"	0.057"
Max Tip Size (2-Guns)	0.043"	0.035"
Max Tip Size (3-Guns)	0.035"	0.031"
Max Tip Size (4-Guns)	0.031"	0.027"
Max Tip Size (5-Guns)	0.025"	0.021"
Max Tip Size (6-Guns)	0.021"	
Max. Operating Pressure	4500 psi	7250 psi
Cycles Per Gallon	15	23
Volumetric Flow per Double Stroke	247 сс	162 cc
CONFIGURATIONS	PART NO.	PART NO.
49 States, Honda	2412275	2412277
California, Honda	2412275X	2412277X
Kohler Engine ¹	2412275K	2412277K
49 States, Honda, 250' GHT ²	2424560	2424561
California, Honda, 250' GHT ²	2424560X	2424561X
Kohler 250' GHT ¹	2424560K	2424561K
0 1: 1 :: 1 :: 0:: 0 1:(104001

Compliant with 2024 California Air Resources Board [CARB] rules at time of printing.

² Configurations comes with 250' Hose, M-8 Gun, 631 High Pressure Tip.

BATTERY-POWERED

IMPACT X[™] 120 18V

Step up to industry-exclusive portability, flexibility, and comfort with the Impact X 120 18V. Optimized for HEA use and featuring three operational configurations so you're ready to go no matter what the job calls for.



FLEXSPRAY[®] PRO 18V

The next generation of handheld sprayer from Titan, FlexSpray Pro 18V cuts the cord to give you more freedom. AMPShare[™] by Bosch[®] 4Ah batteries keep you working all day on a single battery system that interchanges across multiple Titan sprayers while still delivering the power of airless and the control of HVLP into one versatile sprayer.



Features:

Cut The Cord

Lightweight and powerful AMPShare by Bosch battery for fatigue-free operation

Optimized for HEA and Fine Finish Tips

1600 Max psi delivers first-rate low pressure and fine finishing airless performance

Smart Design

- Operate in Backpack, Stationary, and Side-Carry for whatever the jobsite demands
- ▶ 1.25 gallon hopper

	Impact X 120 18V	
SPECIFICATIONS		
Max. Delivery	0.31 gpm	
Max. Operating Pressure	1600 psi	
Max. Tip Size (1-Gun)	HEA .017"	
Batteries Included	2 – 18V 4Ah AMPShare by Bosch Batteries 1 – Battery Charger	
Hopper Capacity	1.25 gal	
Hose Length	9'	
Gun Included	RX-80 2-finger w/517 HEA & 312 Fine Finish Tip	
Part Number	2441253A	

Features:

Cut The Cord

Lightweight and powerful Bosch battery for fatigue-free operation

JetForce Technology®

Delivers control of a 4-stage HVLP and production of airless 413 Tip

Smart Design

Quick change system for front end swaps with a twist

	FlexSpray Pro 18V		
SPECIFICATIONS			
Max. Operating Pressure	4.0 psi		
Batteries Included	2 – 18V 4Ah AMPShare by Bosch Batteries 1 – Battery Charger		
Front Ends Included	FineFinish & FlexFinish®		
Part Number	2443773B		

CAPSPRAY[™] SERIES

HVLP SPRAYERS

High-end woodworking, cabinetry and furniture finishing projects require the high transfer efficiency that only Titan Capspray can deliver. These lightweight, portable, high-viscosity, low-pressure sprayers will apply all fine finishes with speed and precision – maximizing both productivity and profit.

Features:

Powerful Atomization

Legendary power delivers the finest atomization for a superior finish

High Transfer Efficiency

Ranges up to 90%

Dual Air Filtration Available on 95, 105 and 115 models An automotive type air filter on the atomizing air side

Pre-filter On both atomizing air and cooling air sides

Built-In Toolbox

For needles, nozzles, air caps and nozzle wrench

Built-In Cup Holder

Also serves as docking station for Transfer Pump accessory

Dirty Filter Warning Light

Extend the life of your turbine and maintain maximum performance with clean filters

Features:

Superior Performance

A high efficiency 8 psi turbine that delivers like a traditional four-stage for ultimate finish quality

Dual Air Filtration

Easy to replace air filters that filter cooling and atomizing air

Filter Warning Light

Visual assistance for preventative maintenance to ensure optimal unit performance and lifespan

On-Board Toolbox

Easily organize needle nozzle kits, aircaps, cleaning brushes and other tools

Multiple Storage Options

Integrated cup holder fits all HVLP cup guns and secondary gun hook for gravity-feed guns

Maxum II Gun

Adjustable air, fluid, and fan pattern settings for legendary precision and control

	Capspray 75	Capspray 95	Capspray 105	Capspray 115
SPECIFICATIONS				
Air Pressure	7.5 psi	9.5 psi	10.5 psi	11.5 psi
Turbine	3-Stage Tangential	4-Stage Tangential	5-Stage Tangential	6-Stage Tangential
Hose Length	25'	30'	30' and 5' Whip	30' and 5' Whip
Weight	20.5 lbs	21.0 lbs	22.0 lbs	23.0 lbs
Needle Nozzle Set (Additional)			#4	#4, #5
CONFIGURATIONS	PART NO.	PART NO.	PART NO.	PART NO.
With Maxum II Gun	524031	524032		
With Maxum Elite Gun			524033	524034*

*Includes Gravity Cup Accessory.

CAPSPRAY X[™] 80

Need to deliver the high-quality finish your customers expect without breaking your budget? The Capspray X 80 has you covered. Perfect for medium residential and commercial jobs this 8 psi turbine sprayer is powerful, lightweight, and offers an industry-best ROI.



 Capspray X 80 with Maxum II Gun

Capspray 115 with

Maxum Elite Gun

	CAPSPRAY X 80
SPECIFICATIONS	
Air Pressure	8.0 psi
Hose Length	25'
Gun	Maxum II
Weight	9 lbs
Part Number	2423009

Capspray X 80 includes 25' Air Hose, Maxum II Gun, #3 Needle Nozzle, & Cleaning Brushes

AIRLESS AND AIR-ASSISTED

Features:

High Production Fine Finishing

All Architectural Coatings From clears to finish-quality latex.

Zero Pressure Fluctuation

ED 655 Plus

A compact, lightweight system that's easy to use, easy to transport, and dependable. For fine finish projects and the contractors who tackle them, we designed the Titan ED 655 Plus.

AirCoat™

The speed and power of an airless sprayer combined with the precise control and transfer efficiency of an HVLP sprayer in a single, incredibly efficient application system – the Titan AirCoat[™] Air-Assisted Airless Sprayer enables you to apply coatings in an air-assisted mode to deliver ultra-fine atomization and higher transfer efficiency. Switch to airless mode to apply a broad range of interior and exterior coatings with the production speed you expect from Titan.

MultiFinish[™] 440

The MultiFinish 440 is designed as a high production fine finish air-assisted airless system built on the legendary Titan 440 airless sprayer platform offering two systems in one. It sprays all coatings with little or no reduction.

	AIRLESS	AIR ASSIST	ED AIRLESS
	ED 655 Plus	AirCoat	MultiFinish 440
SPECIFICATIONS			
Max. Delivery	0.35 gpm	0.35 gpm	0.54 gpm
Max. Tip Size (1-Gun)	0.017"	0.017"	0.023"
Max. Fluid Pressure	2800 psi	2800 psi	3300 psi
Max. Air Pressure		35 psi	35 psi
Weight	27 lbs	56 lbs	90 lbs
Fluid/Air Hose Length	50' with 3' Whip	50' with 5' Whip	50'
Spray Gun	RX-80 [™]	GM3600	GM3600
Pump Motor	1/2 hp TEFC	1/2 hp TEFC	7/8 hp PMDC
Part Number	508090	0508074A	524029



ACCESSORIES:

GM 3600 Pro Gun with Reversible Tip Guard 2404548

This design offers ergonomic comfort and a reversible tip system without sacrificing finish quality. Comes with a push-in filter and works with all standard reversible airless and fine finish tips.

GM 3600 Pro Gun with Flat Tip Guard 2412194 Includes a 9/20 flat tip.

Airless & Air Hose 50-Foot Set 524333



13

POWRCOAT[™] SERIES

Features:

Premium is Standard

Minimal Maintenance

Titan's proven severe-duty fluid section with selfadjusting packings keeps you working in the most demanding of jobsites

Anti-icing Motor

Ensures continuous operation in all environments

Power to Handle Any Job

The PowrCoat series pressure ranges from 3000 to 7200 psi

Flow

Outputs from one to four gallons per minute

Self-adjusting

No packing nut to adjust

Severe Service[™] Fluid Section is Standard

- Severe-service paint pumps and high-efficiency air motors are standard on all models
- PowrCoat piston is engineered to provide unmatched chemical and solvent resistance while creating an ultrasmooth surface that operates with a smooth stroke, minimizing friction and wear
- Tungsten carbide valve seats provide maximum life and smooth, efficient operation with hardened stainless steel check balls

AirCare[™] System

- Complete FRL (Filter, Regulator, Lubricator) standard for optimal durability with every PowrCoat
- Automatic draining moisture trap
- Easy access air filter and lubrication reservoir

Models for virtually any application, including architectural, finishing, industrial maintenance, corrosion control, roofing, waterproofing and marine protective coatings.



	PowrCoat 730	PowrCoat 745	PowrCoat 940	PowrCoat 960	PowrCoat 1045	PowrCoat 1064	PowrCoat 1072
SPECIFICATIONS							
Air Motor Diameter	7"	7"	9"	9"	10"	10"	10"
Ratio	30:1	45:1	40:1	60:1	45:1	64:1	72:1
Stroke Length	4"	4"	4"	4"	4.75"	4.75"	4.75"
Fluid Output per Cycle	182cc	114cc	182cc	114cc	254cc	188cc	167cc
Max. Recommended Output	4.0 gpm	2.8 gpm	4.0 gpm	2.8 gpm	4.0 gpm	3.0 gpm	2.7 gpm
Max. Recommended Vol. Requirements	98 cfm	102 cfm	116 cfm	128 cfm	172 cfm	171 cfm	173 cfm
Max. Air Input Pressure	100 psi	100 psi	100 psi				
Max. Operating Pressure	3000 psi	4500 psi	4000 psi	6000 psi	4500 psi	6400 psi	7200 psi
CONFIGURATIONS	PART NO.	PART NO.	PART NO.				
Cart (bare)	0533730C	0533745C	0533940C	0533960C	05331045C	05331064C	05331072C

POWRLINER[™] SERIES

Features:

Large 16" Pneumatic Tires

Increases portability and makes traveling over rough surfaces easier

Swing Back Frame Design

Increases operator leverage and reduces fatigue

Electric Engine Start

Quick and convenient way to start projects (Models 6955 and 8955 only)





martArm Pivot System SmartArm Lift System



DeadLock Handlebars[™]

Infinitely adjustable in 3 planes Available on PowrLiner 4955, 6955, and 8955 units.

SmartArm[™] Pivots and lifts, making line adjustments and transportation quick and easy Available on PowrLiner 4955, 6955, and 8955 units.

PowrCenter[™] Dashboard Convenient access to user controls, tip holder, and cup holder. Designs vary by model Engineered and built with technology to deliver best-in-class, sharp and consistent line quality on a variety of surfaces including concrete, parking lots, and athletic fields.



PowrLiner 850

PowrLiner 8955

	PowrLiner 850	PowrLiner 3500	PowrLiner 3500S	PowrLiner 3500 72V	PowrLiner 4955	PowrLiner 6955	PowrLiner 8955
SPECIFICATIONS							
Max Delivery	0.33 gpm	0.75 gpm	0.75 gpm	0.75 gpm	1.25 gpm	2.10 gpm	2.50 gpm
Max Operating Pressure	3000 psi	3300 psi	3300 psi	3300 psi	3300 psi	3300 psi	3300 psi
Max Tip Size (1-Gun)	0.021"	0.027"	0.027"	0.027"	0.034"	0.047"	0.054"
Max Tip Size (2-Guns)					0.025"	0.031"	0.038"
Power Source	37.7cc 4-stroke (Gas)	Honda GX120 (Gas)	Honda GX120 (Gas)	Honda eGX (72 Volt Battery)	Honda GX120 (Gas)	Honda GX160 (Gas)	Honda GX200 (Gas)
Pump Drive	Clutch Driven	Clutchless Sealed Hydraulic	Clutchless Sealed Hydraulic	Clutchless Sealed Hydraulic	Hydraulic	Hydraulic	Hydraulic
Part Number	0290005A	0537015A	2417440A	2445730B	0290052H	0290053H	0290054H

LazyLiner Series Specifications

	LAZYLINER PRO	LAZYLINER ELITE
DESCRIPTION		
Gas Engine	Honda GX160	Honda GX200
Start	Pull	Electric
Forward Speed	0 - 12 mph (0 - 19 kph)	0 - 12 mph (0 - 19 kph)
Reverse Speed	0 - 7 mph (0 - 11 kph)	0 - 7 mph (0 - 11 kph)
Bumper / Engine Protection Bar	Optional: Part No. 2423493	Included
100W Lamp Coil Charging System	No	Yes ¹
Part Number	0290041H	0290040H

¹ Allows additional accessories (lasers, lights, etc.) to directly access on-board electrical power

 Compatible with PL2850, PL3500, PL3500S, PL4500, PL4900XLT, PL4950, PL4955, PL6900XLT, PL6950, PL6955, PL8900XLT, PL8950, PL8955

• Line Striper Hitch Kit required and sold separately

Hitch Kits

CONFIGURATION	KIT PART NO.
PowrLiner 2850	0290043Z
PowrLiner 3500, 3500S, 4500	537935
PowrLiner 4955, 6955, 8955 PowrLiner 4950, 6950, 8950	2430599
PowrLiner 4900XLT, 6900XLT, 8900XLT	2430599 + 0290489A (updated axle with pre-drilled thru-holes)

LazyLiner drivers are not shipped with a hitch.

15

AIRLESS SPRAY GUNS

RX-PRO® AIRLESS SPRAY GUN

The RX-Pro airless spray gun redefines spraying with unmatched comfort and durability including on-board tools like the built-in filter wrench that make jobsite life easier.



The RX-80 features all-metal construction with tungsten carbide ball valve and seat for added durability. The RX-80 is available in 2- or 4-finger configuration.



*Includes additional 3' whip hose and a 2-finger trigger.

16

AIRLESS SPRAY GUNS



HANDLE HEAVY AND HIGH PRESSURE COATINGS WITH EASE

Titan S-Series stainless steel spray guns hold up under extreme pressure and are built for contractors that need to spray at pressures from 3900–7700 psi. The S-Series can handle corrosive coatings due to the stainless steel fluid passage. The tungsten carbide ball valve and seat ensure long life and durability.

S-3 / S-7 Airless Gun

- In-handle filter
- Easy four-finger trigger pull
- Swivel reduces hose kinks
- S-3 is pressure rated at 3900 psi (26.9 MPa)
- S-7 is pressure rated at 7700 psi (53.1 MPa)

DESCRIPTION	PART NO.
S-3 Gun with TR ¹ Tip	550-250
S-3 Gun, Hose and Tip Kit	550065
S-3 Repair Kit	550-275
S-7 Gun with 1/4" Swivel	550-260
S-7 Gun with 3/8" Swivel	550-270
S-7 Repair Kit	550-276

The M-Series guns are designed to handle the heaviest and harshest coatings with an unobstructed large fluid chamber and extremly durable stainless steel.

M-4 / M-8 Mastic Guns

- Straight-line fluid passage allows maximum flow
- Angled handle for increased comfort
- Adjustable needle packing prolongs the life of critical wear parts
- Swivel allows freedom of movement without hose kinking
- Lightweight metal construction
- M-4 is pressure rated at 3600 psi (24.8 MPa)
- M-8 is pressure rated at 7700 psi (53.1 MPa)

DESCRIPTION	PART NO.
M-4 Mastic Gun with 3/8" Swivel	289013
M-8 Mastic Gun with 1/4" Swivel	289014
M-8 Mastic Gun with 3/8" Swivel	2425442
M-4/M-8 Repair Kit	2348175



AIRLESS SPRAY TIPS

HEA HIGH EFFICIENCY

HEA REVERSIBLE TIP

- Optimized to spray all architectural paints and coatings at 1,000 psi at production speed
- Decreases overspray up to 55% allowing contractors to spray more
- Less pressure equals less stress extending pump life and extending time between repacks
- Two times the life of a standard reversible tip

Highly Efficient Fan Pattern

- Feathered edge provides consistent coverage
- More forgiving pattern that decreases runs and drips
- Less spray gun kickback when triggered providing more control and less overspray
- Fits all industry standard guards

HEA Tips 330-XXX

				ORIF	ICE SIZ	E (INC	HES)	
	INCHES	MM	0.011	0.013	0.015	0.017	0.019	0.021
_	4-6	102-152	211	213				
Ē	6-8	152-203	311	313				
N	8-10	203-254	411	413	415	417		421
PATTERN WIDTH	10-12	254-305			515	517	519	521
PAT	12-14	305-356			615	617	619	621
FAN	Flow (gpm)		0.09	0.12	0.18	0.24	0.31	0.47
	Flow (lpm)		0.34	0.45	0.68	0.91	1.17	1.79



Maximum Working Pressure: 5000 psi (34.5 MPa)





Latex paint through a standard 517 tip at 1,000 psi

427

TR

Latex paint through a HEA 517 tip at 1,000 psi

Line Striping Tips 697-XXX

					ORI	FICE SIZ	E (INCH	IES)		
	INCHES	MM	0.013	0.015	0.017	0.019	0.021	0.023	0.025	0.027
臣	2	51		215	217	219				
WIDTH	4	102	413	415	417	419	421	423		427
ERN	6	152		615	617	619	621			
PATTERN	8-10	203-254					821	823		
FAN	Flow (gpm)		0.18	0.24	0.31	0.39	0.47	0.57	0.67	0.78
	Flow (lpm)		0.68	0.91	1.17	1.47	1.78	2.15	2.53	2.95

Maximum Working Pressure: 5000 psi (34.5 MPa)

High Pressure Tips 696-XXX

										E (INC						
	INCHES	MM	0.011	0.013	0.015	0.017	0.019	0.021	0.023	0.025	0.027	0.031	0.035	0.037	0.039	0.043
	4-6	102-152	211	213												
	6-8	152-203			315	317	319	321	323	325						
WIDTH	8–10	203-254			415	417	419									
Ň	10-12	254-305			515	517	519	521	523	525	527	531	535	537		543
TERN	12-14	305-356									627					
PAT	14-16	356-406						721								
FAN	16–18	406-457											835		839	
	18–20	457-508							923							
	Flow (gpm)		0.13	0.18	0.24	0.31	0.39	0.47	0.57	0.67	0.78	1.03	1.32	1.40	1.64	1.99
	Flow (Ipm)		0.45	0.68	0.91	1.17	1.47	1.78	2.15	2.53	2.95	3.89	4.99	5.29	6.20	7.52
	Flow (lpm)				0.91	1.17	1.47	1.78	2.15	2.53	2.95	3.89	4.99	5.29	6.20	7.52



Maximum Working Pressure: 7700 psi (53.1 MPa)

HIGH QUALITY SC-6+ REVERSIBLE TIP

- ▶ The industry's longest-lasting orifice
- Up to 22% wider fan pattern
- Fits all Titan and most industry standard guards



SC-6+ Tips 662-XXX

								ORI	FICE WID	TH (INC	HES)					
	INCHES	ММ	0.007	0.009	0.011	0.013	0.015	0.017	0.019	0.021	0.023	0.025	0.027	0.029	0.031	0.035
_	4—6	102-152	207	209	211	213	215	217	219							
İ	6—8	152-203		309	311	313	315	317	319	321		325				
N N	8–10	203-254		409	411	413	415	417	419	421						
TTE:	10-12	254-305			511	513	515	517	519	521	523	525			531	535
FAN PATTERN WIDTH	12-14	305-356		609	611	613	615	617	619	621	623	625	627	629	631	635
Æ	Flow (gpm)		0.05	0.09	0.13	0.18	0.24	0.31	0.39	0.47	0.57	0.67	0.78	0.91	1.03	1.32
	Flow (Ipm)		0.19	0.34	0.45	0.68	0.91	1.17	1.47	1.78	2.15	2.53	2.95	3.44	3.89	4.99



Maximum Working Pressure: 5000 psi (34.5 MPa)

SC-6+ Fine Finishing Tips 671-XXX

			0	RIFICE SIZ	E (INCHE	S)
	INCHES	ММ	0.008	0.010	0.012	0.014
	4–6	102-152	208	210	212	214
Ē	6—8	152-203	308	310	312	314
Ň	8–10	203-254	408	410	412	414
FAN PATTERN WIDTH	10-12	254-305		510	512	514
N PA	12-14	305-356			612	
Ŧ	Flow (gpm)		0.07	0.11	0.16	0.21
	Flow (lpm)		0.26	0.42	0.60	0.79

Maximum Working Pressure: 5000 psi (34.5 MPa)



Flow rates are calculated at 2000 psi with water.





WEARGUARD CONVENIENCE PROGRAM KEEPS YOU UP AND RUNNING



When you purchase a new Titan sprayer, you're able to take advantage of our exclusive WearGuard Convenience Program. Protect your investment by purchasing a spare fluid section or PermaStroke kit at a discounted rate. Save yourself the time and frustration of an extra trip or waiting for parts to arrive in the event that your sprayer goes down. When you have a backup fluid section or PermaStroke kit on hand, replacement can quickly be made without leaving the jobsite and doesn't require special tools. The bottom line is that WearGuard keeps you up and running.

Not interested in purchasing a spare fluid section? We also offer the option of a free packing kit on select sprayers.

For more information on pricing and how to order, go to:

www.titanwearguard.com or scan the QR code.





KEEP TITAN WITH YOU WHEREVER YOU GO



MyTitan[™] gives you immediate access to all things Titan. Anywhere, anytime on your computer or mobile device. MyTitan gives you everything you need to get the most out of your sprayers, all in one place, no matter where the workday takes you. MyTitan is designed to make your life easier, your business more efficient, and your day more productive-so you can stay ahead of the game, do more in less time, and never lose track of another detail.

For more information on this new app, go to:

www.titantool.com/ mytitan-welcome or scan the QR code.





ONLINE REWARD REDEMPTION NO CLIPPING. NO STAMPS. NO HASSLES.

For more information and to see current promotions, go to: www.titantool.com/thor-promos or scan the QR code.



All information contained in this brochure is based on the latest information available at the time of printing. Titan reserves the right to make changes at any time, without notice. Due to continuous innovation, specifications may progressively change. Contact one of our dependable sales reps or call our dedicated customer service team for more information.